




# LOCKING DEVICE

Edition. 21.2

- **LKB** FOR GM - GN
- **LKF** FOR GE - GB - GHP - GPK
- **LKR** FOR GR
- **SECURITY BLOCK** FOR GE - GB  
GHP - GPK (except DN6) - G3/4K
- **LKS** FOR SBF - SBF-W






## LKB FOR GM - GN

| TYPE   | DN       | SW        | ØF   | MATERIAL        | TREATMENT  | WEIGHT   | ITEM CODE    |
|--------|----------|-----------|------|-----------------|------------|----------|--------------|
| LK6-B  | 6-10-13  | mm 9      | 9,5  | CARBON STEEL    | GALVANIZED | kg 0,178 | KMK00LK6B2Z  |
|        |          | inch 0,35 | 0,37 |                 |            | lb 0,39  |              |
| LK6-B  | 6-10-13  | mm 9      | 9,5  | STAINLESS STEEL | -          | kg 0,178 | KMK00LK6B6H  |
|        |          | inch 0,35 | 0,37 |                 |            | lb 0,39  |              |
| LK20-B | 20-25    | mm 14     | 10,5 | CARBON STEEL    | GALVANIZED | kg 0,413 | KMK00LK20B2Z |
|        |          | inch 0,55 | 0,41 |                 |            | lb 0,91  |              |
| LK20-B | 20-25    | mm 14     | 10,5 | STAINLESS STEEL | -          | kg 0,413 | KMK00LK20B6H |
|        |          | inch 0,55 | 0,41 |                 |            | lb 0,91  |              |
| LK32-B | 32-40-50 | mm 17     | 10,5 | CARBON STEEL    | GALVANIZED | kg 0,53  | KMK00LK32B2Z |
|        |          | inch 0,67 | 0,41 |                 |            | lb 1,17  |              |
| LK32-B | 32-40-50 | mm 17     | 10,5 | STAINLESS STEEL | -          | kg 0,53  | KMK00LK32B6H |
|        |          | inch 0,67 | 0,41 |                 |            | lb 1,17  |              |

# LOCKING DEVICE

## KITS




### LKF FOR GE - GB - GHP - GPK

| TYPE   | DN             | SW        | ØF   | MATERIAL        | TREATMENT  | WEIGHT   | ITEM CODE    |
|--------|----------------|-----------|------|-----------------|------------|----------|--------------|
| LK6-MF | 6 only for GPK | mm 6      | 6,8  | CARBON STEEL    | GALVANIZED | kg 0,043 | K0K00LK6MF2Z |
|        |                | inch 0,24 | 0,27 |                 |            | lb 0,09  |              |
| LK6-F  | 6-10-13        | mm 9      | 9,5  | CARBON STEEL    | GALVANIZED | kg 0,043 | K0K00LK6F2Z  |
|        |                | inch 0,35 | 0,37 |                 |            | lb 0,09  |              |
| LK6-F  | 6-10-13        | mm 9      | 9,5  | STAINLESS STEEL | -          | kg 0,043 | K0K00LK6F6H  |
|        |                | inch 0,35 | 0,37 |                 |            | lb 0,09  |              |
| LK20-F | 20-25          | mm 14     | 9,5  | CARBON STEEL    | GALVANIZED | kg 0,121 | K0K00LK20F2Z |
|        |                | inch 0,55 | 0,37 |                 |            | lb 0,27  |              |
| LK20-F | 20-25          | mm 14     | 9,5  | STAINLESS STEEL | -          | kg 0,121 | K0K00LK20F6H |
|        |                | inch 0,55 | 0,37 |                 |            | lb 0,27  |              |
| LK32-F | 32-40-50       | mm 17     | 9,5  | CARBON STEEL    | GALVANIZED | kg 0,187 | K0K00LK32F2Z |
|        |                | inch 0,67 | 0,37 |                 |            | lb 0,41  |              |
| LK32-F | 32-40-50       | mm 17     | 9,5  | STAINLESS STEEL | -          | kg 0,187 | K0K00LK32F6H |
|        |                | inch 0,67 | 0,37 |                 |            | lb 0,41  |              |




Padlock  
not included



## LKR FOR GR

| TYPE   | DN       | SW        | ØF   | MATERIAL        | TREATMENT  | WEIGHT  | ITEM CODE     |
|--------|----------|-----------|------|-----------------|------------|---------|---------------|
| LKR13  | 13       | mm 9      | 9,5  | CARBON STEEL    | GALVANIZED | kg 0,1  | K0K00LKR132Z  |
|        |          | inch 0,35 | 0,37 |                 |            | lb 0,22 |               |
| LKR13  | 13       | mm 9      | 9,5  | STAINLESS STEEL | -          | kg 0,1  | K0K00LKR136H  |
|        |          | inch 0,35 | 0,37 |                 |            | lb 0,22 |               |
| LKR20  | 20-25    | mm 14     | 9,5  | CARBON STEEL    | GALVANIZED | kg 0,18 | K0K00LKR202Z  |
|        |          | inch 0,55 | 0,37 |                 |            | lb 0,40 |               |
| LKR20  | 20-25    | mm 14     | 9,5  | STAINLESS STEEL | -          | kg 0,18 | K0K00LKR206H  |
|        |          | inch 0,55 | 0,37 |                 |            | lb 0,40 |               |
| LKR32  | 32-40-50 | mm 17     | 9,5  | CARBON STEEL    | GALVANIZED | kg 0,34 | K0K00LKR322Z  |
|        |          | inch 0,67 | 0,37 |                 |            | lb 0,75 |               |
| LKR32  | 32-40-50 | mm 17     | 9,5  | STAINLESS STEEL | -          | kg 0,34 | K0K00LKR326H  |
|        |          | inch 0,67 | 0,37 |                 |            | lb 0,75 |               |
| LKR65  | 65-80    | mm 19     | 9,5  | CARBON STEEL    | GALVANIZED | kg 0,55 | K0K00LKR652Z  |
|        |          | inch 0,75 | 0,37 |                 |            | lb 1,21 |               |
| LKR65  | 65-80    | mm 19     | 9,5  | STAINLESS STEEL | -          | kg 0,55 | K0K00LKR656H  |
|        |          | inch 0,75 | 0,37 |                 |            | lb 1,21 |               |
| LKR100 | 100      | mm 24     | 9,5  | CARBON STEEL    | GALVANIZED | kg 1,08 | K0K00LKR1002Z |
|        |          | inch 0,94 | 0,37 |                 |            | lb 2,38 |               |
| LKR100 | 100      | mm 24     | 9,5  | STAINLESS STEEL | -          | kg 1,08 | K0K00LKR1006H |
|        |          | inch 0,94 | 0,37 |                 |            | lb 2,38 |               |




## SECURITY BLOCK FOR GE - GB - GHP - GPK (EXCEPT DN6) - G3/4K

| TYPE | DN                               | SW        | ØF   | MATERIAL     | TREATMENT  | WEIGHT   | ITEM CODE   |
|------|----------------------------------|-----------|------|--------------|------------|----------|-------------|
| SB6  | 6-10-13<br>6 only for G3/4K      | mm 9      | 6,8  | CARBON STEEL | GALVANIZED | kg 0,066 | K0B00SB61Z  |
|      |                                  | inch 0,35 | 0,27 |              |            | lb 0,15  |             |
| SB20 | 20-25<br>10-13-20 only for G3/4K | mm 14     | 9,5  | CARBON STEEL | GALVANIZED | kg 0,221 | K0B00SB201Z |
|      |                                  | inch 0,55 | 0,37 |              |            | lb 0,49  |             |
| SB32 | 32-40-50<br>25 only for G3/4K    | mm 17     | 9,5  | CARBON STEEL | GALVANIZED | kg 0,24  | K0B00SB321Z |
|      |                                  | inch 0,67 | 0,37 |              |            | lb 0,53  |             |


# LOCKING DEVICE

## KITS



### LKS FOR SBF - SBF-W

| TYPE         | DN       | ANSI                           | SW   |      | ØF   | MATERIAL        | TREATMENT  | WEIGHT |      |
|--------------|----------|--------------------------------|------|------|------|-----------------|------------|--------|------|
| LK13 - S     | 13       | 150-300-600                    | mm   | 9    | 6,5  | CARBON STEEL    | GALVANIZED | kg     | 0,03 |
|              |          |                                | inch | 0,35 | 0,26 |                 |            | lb     | 0,07 |
| LK13 - S     | 13       | 150-300-600                    | mm   | 9    | 6,5  | STAINLESS STEEL | -          | kg     | 0,03 |
|              |          |                                | inch | 0,35 | 0,26 |                 |            | lb     | 0,07 |
| LK20 - S 150 | 20       | 150                            | mm   | 14   | 6,5  | CARBON STEEL    | GALVANIZED | kg     | 0,07 |
|              |          |                                | inch | 0,55 | 0,26 |                 |            | lb     | 0,15 |
| LK20 - S 150 | 20       | 150                            | mm   | 14   | 6,5  | STAINLESS STEEL | -          | kg     | 0,07 |
|              |          |                                | inch | 0,55 | 0,26 |                 |            | lb     | 0,15 |
| LK20 - S     | 20-25    | 150 (only for DN25)<br>300-600 | mm   | 14   | 6,5  | CARBON STEEL    | GALVANIZED | kg     | 0,07 |
|              |          |                                | inch | 0,55 | 0,26 |                 |            | lb     | 0,15 |
| LK20 - S     | 20-25    | 150 (only for DN25)<br>300-600 | mm   | 14   | 6,5  | STAINLESS STEEL | -          | kg     | 0,07 |
|              |          |                                | inch | 0,55 | 0,26 |                 |            | lb     | 0,15 |
| LK32 - S     | 32-40-50 | 150-300-600                    | mm   | 17   | 6,5  | CARBON STEEL    | GALVANIZED | kg     | 0,08 |
|              |          |                                | inch | 0,67 | 0,26 |                 |            | lb     | 0,18 |
| LK32 - S     | 32-40-50 | 150-300-600                    | mm   | 17   | 6,5  | STAINLESS STEEL | -          | kg     | 0,08 |
|              |          |                                | inch | 0,67 | 0,26 |                 |            | lb     | 0,18 |
| LK80 - S     | 80       | 150-300-600                    | mm   | 19   | 10   | CARBON STEEL    | GALVANIZED | kg     | 0,16 |
|              |          |                                | inch | 0,75 | 0,39 |                 |            | lb     | 0,35 |
| LK80 - S     | 80       | 150-300-600                    | mm   | 19   | 10   | STAINLESS STEEL | -          | kg     | 0,16 |
|              |          |                                | inch | 0,75 | 0,39 |                 |            | lb     | 0,35 |
| LK100 - S    | 100      | 150-300-600                    | mm   | 24   | 12   | CARBON STEEL    | GALVANIZED | kg     | 0,3  |
|              |          |                                | inch | 0,94 | 0,47 |                 |            | lb     | 0,66 |
| LK100 - S    | 100      | 150-300-600                    | mm   | 24   | 12   | STAINLESS STEEL | -          | kg     | 0,3  |
|              |          |                                | inch | 0,94 | 0,47 |                 |            | lb     | 0,66 |



## LKF LS (LIMIT SWITCH) FOR GE - GHP - GPK (EXCEPT DN6)

| TYPE      | DN       | SW        | ØF   | MATERIAL        | TREATMENT  | WEIGHT   | ITEM CODE       |
|-----------|----------|-----------|------|-----------------|------------|----------|-----------------|
| LK6-F LS  | 6-10-13  | mm 9      | 9,5  | CARBON STEEL    | GALVANIZED | kg 0,019 | K11A00207AA000Z |
|           |          | inch 0,35 | 0,37 |                 |            | lb 0,04  |                 |
| LK6-F LS  | 6-10-13  | mm 9      | 9,5  | STAINLESS STEEL | -          | kg 0,019 | K11A00207AA000H |
|           |          | inch 0,35 | 0,37 |                 |            | lb 0,04  |                 |
| LK20-F LS | 20-25    | mm 14     | 9,5  | CARBON STEEL    | GALVANIZED | kg 0,056 | K11A00208AA000Z |
|           |          | inch 0,55 | 0,37 |                 |            | lb 0,12  |                 |
| LK20-F LS | 20-25    | mm 14     | 9,5  | STAINLESS STEEL | -          | kg 0,056 | K11A00208AA000H |
|           |          | inch 0,55 | 0,37 |                 |            | lb 0,12  |                 |
| LK32-F LS | 32-40-50 | mm 17     | 9,5  | CARBON STEEL    | GALVANIZED | kg 0,055 | K11A00209AA000Z |
|           |          | inch 0,67 | 0,37 |                 |            | lb 0,12  |                 |
| LK32-F LS | 32-40-50 | mm 17     | 9,5  | STAINLESS STEEL | -          | kg 0,055 | K11A00209AA000H |
|           |          | inch 0,67 | 0,37 |                 |            | lb 0,12  |                 |